



INDUSTRIAL PAINT BOOTHS

GLOBAL FINISHING SOLUTIONS™

Quick Reference Chart – Most Popular Models and Options

BENCH / FLOOR INDUSTRIAL SPRAY BOOTHS							
Model	Inside Dimensions (W, H, D)	Outside Dimensions (W, H, D)	HP	CFM	Fan Diameter	# Light Fixtures	Optional Exhaust Stack Kit
4' HIGH	Bench Top Booth (without stand)						
	FP-3-BT	3'0" x 2'10" x 2'	3'6" x 3'2" x 3'2"	1/2	900	18"	0
	Bench Top Booth (with stand)						
	FP-3	3'0" x 2'10" x 2'	3'6" x 3'2" x 3'2"	1/2	900	18"	0
7' INSIDE HEIGHT	FP-5	5'0" x 4'2" x 3'0"	5'6" x 7'2" x 6'2"	1	2000	18"	1
	FP-7	7'6" x 4'2" x 3'4"	7'11" x 7'2" x 6'2"	1	3000	18"	1
	FP-676-125	5'8" x 7' x 6'	6' x 7'2" x 9'2"	1	5250	24"	1
	FP-876-125	7'8" x 7' x 6'	8' x 7'2" x 9'2"	2	7000	24"	1
8' INSIDE HEIGHT	FP-1076-125	9'8" x 7' x 6'	10' x 7'2" x 9'2"	5	8750	24"	2
	FP-1276-125	11'8" x 7' x 6'	12' x 7'2" x 9'2"	2	10500	34"	2
	FP-1476-125	13'8" x 7' x 6'	14'4" x 7'8" x 9'2"	3	12250	34"	2
	FP-1676-125	15'8" x 7' x 6'	16'4" x 7'8" x 9'2"	3	14000	34"	2
10' INSIDE HEIGHT	FP-1876-125	17'8" x 7' x 6'	18'4" x 7'8" x 9'2"	5	15750	34"	2
	FP-2076-125	19'8" x 7' x 6'	20'4" x 7'8" x 9'2"	5	17500	34"	4
	FP-686-125	5'8" x 8' x 6'	6' x 8'2" x 9'2"	2	8000	24"	1
	FP-886-125	7'8" x 8' x 6'	8' x 8'2" x 9'2"	3	9000	24"	1
12' INSIDE HEIGHT	FP-1086-125	9'8" x 8' x 6'	10' x 8'2" x 9'2"	2	10000	34"	2
	FP-1286-125	11'8" x 8' x 6'	12' x 8'2" x 9'2"	3	12000	34"	2
	FP-1486-125	13'8" x 8' x 6'	14'4" x 8'8" x 9'2"	3	14000	34"	2
	FP-1686-125	15'8" x 8' x 6'	16'4" x 8'8" x 9'2"	5	16000	34"	2
12' INSIDE HEIGHT	FP-1886-125	17'8" x 8' x 6'	18'4" x 8'8" x 9'2"	5	18000	34"	2
	FP-2086-125	19'8" x 8' x 6'	20'4" x 8'8" x 9'2"	7 1/2	20000	34"	4
	FP-6106-125	5'8" x 10' x 6'	6' x 10'2" x 9'2"	2	7500	24"	1
	FP-8106-125	7'8" x 10' x 6'	8' x 10'2" x 9'2"	2	10000	34"	1
12' INSIDE HEIGHT	FP-10106-125	9'8" x 10' x 6'	10' x 10'2" x 9'2"	3	12500	34"	2
	FP-12106-125	11'8" x 10' x 6'	12' x 10'2" x 9'2"	3	15000	34"	2
	FP-14106-125	13'8" x 10' x 6'	14'4" x 10'8" x 9'2"	5	17500	34"	2
	FP-16106-125	15'8" x 10' x 6'	16'4" x 10'8" x 9'2"	7 1/2	20000	34"	2
12' INSIDE HEIGHT	FP-18106-125	17'8" x 10' x 6'	18'4" x 10'8" x 10'2"	5	22500	40"	2
	FP-20106-125	19'8" x 10' x 6'	20'4" x 10'8" x 10'2"	7 1/2	25000	40"	4
	FP-6126-125	5'8" x 12' x 6'	6' x 12'2" x 9'2"	2	9000	24"	1
	FP-8126-125	7'8" x 12' x 6'	8' x 12'2" x 9'2"	3	12000	34"	1
12' INSIDE HEIGHT	FP-10126-125	9'8" x 12' x 6'	10' x 12'2" x 9'2"	3	15000	34"	2
	FP-12126-125	11'8" x 12' x 6'	12' x 12'2" x 9'2"	3	18000	34"	2
	FP-14126-125	13'8" x 12' x 6'	14'4" x 12'8" x 10'2"	5	21000	40"	2
	FP-16126-125	15'8" x 12' x 6'	16'4" x 12'8" x 10'2"	7 1/2	24000	40"	2
12' INSIDE HEIGHT	FP-18126-125	17'8" x 12' x 6'	18'4" x 12'8" x 10'2"	7 1/2	27000	40"	2
	FP-20126-125	19'8" x 12' x 6'	20'4" x 12'8" x 9'2"	3	30000	(2) 34"	4

REQUIRED OPTION: 3-WAY SAFETY VALVE - Part #242-124

3 Port/2-Position air valve prevents spraying with air-assist systems when booth exhaust is off. Compressed air between valve and spray equipment is vented out when exhaust is shut off. 120-volt coil standard. 3/4" ports standard.

OTHER OPTIONS

- **EXHAUST KIT** includes (1) duct 3' long with cleanout door, (3) plain duct 3' long, stack head with auto damper.
- **ELECTRICAL CONTROL PANELS** Fully assembled and tested **UL 508 LISTED**.

COMPLETE PANEL INCLUDES:		SPRAY BOOTH	Motor HP	230 VOLT Single-Phase	Three-Phase 3 Wire Sys.	4 Wire Sys.	480-Volt 3 Wire Sys.	Three-Phase 4 Wire Sys.
•UL Listed NEMA 1 Enclosure •Main Disconnect Switch •Light Switch •Magnetic Motor Starter with Fuse Protection •Operative On/Off Buttons •Fire Protection Interlock •Dry Contact for Customer Use		APPLICATION	1/4-1	CP1-12301	CP1-12303	-4	CP1-14803	-4
			2	CP1-22301	CP1-22303	-4	CP1-24803	-4
		Single Motor,	3	CP1-32301	CP1-32303	-4	CP1-34803	-4
		Up to 6 110-	5	CP1-52301	CP1-52303	-4	CP1-54803	-4
		Volt Light	7½	CP1-72301	CP1-72303	-4	CP1-74803	-4
		Fixtures	10		CP1-102303	-4	CP1-104803	-4
			15		CP1-152303	-4	CP1-154803	-4

Dallas, TX • Barrie, ON • Osseo, WI • Mexico
800-848-8738 • www.globalfinishing.com

All designs, specifications and components are subject to change at the manufacturer's sole discretion at any time without notice. Data published herein is informational in nature and shall not be construed to warrant suitability of the unit for any particular purpose as performance may vary with the conditions encountered.